



Allante



AL-890 Tundra



AL-891 Harvest



AL-892 Magnolia



AL-893 River Blue



AL-894 Meadow



AL-895 Hideaway



AL-808 Grey



AL-896 Sea Cruise




AL-897 Reef



AL-862 Lt. Neutral



AL-856 Pearl Grey



AL-816 Cadet Blue



AL-898 Parrot



AL-899 Khaki



AL-870 Med. Grey



AL-806 Ash



AL-818 Galaxy



AL-900 Tumbleweed



AL-804 Charcoal




AL-802 Black



AL-821 Regimental Blue

Allante




AL-810 White



AL-846 Bisque



AL-854 Lt. Parchment



AL-809 Nu-Shale



AL-827 Sea Oyster



AL-844 Cream



AL-864 Lt. Sand



AL-824 Nu-Antelope



AL-901 Cayenne



AL-902 Butterscotch



AL-903 Twine



AL-874 Lt. Sandlewood



AL-877 Nu-Red



AL-904 Mango



AL-868 Teak



AL-872 Med. Neutral



AL-836 Wine



AL-838 Cinnamon



AL-860 Beechwood



AL-835 Dk. Pewter



AL-832 Burgundy



AL-840 Espresso



AL-876 Med. Beige



AL-828 Elephant

Specifications

Width: 54 inches

Roll Size: 40 yards

Weight: 29.25 ± 2 oz per linear yard

Thickness: 45 ± 5 mils

Cold Crack: -25°F

1000 Hours WeatherOmeter

Abrasion Resistance: No significant wear after 100,000 double rubs with #8 cotton duck using the Wyzenbeek test method

Features & Benefits

- Mildew Resistant
- Made in North America
- Bromine-free, No Halogenated Flame Retardants (HFRs)
- REACH compliant
- RoHS Compliant
- Non Toxic
- No heavy metals
- No Mercury
- No Bisphenol A (BPA)
- No Ozone Depleting Chemicals
- No PBT's (Persistent Bio accumulative and Toxic Chemicals)
- Contains bio-based renewable ingredients

Recommended Applications

Automotive
Hospitality
General Upholstery
Residential/Home Office
Hotel/Motel
RV
Work Stations
Corporate

Content

Vinyl

Backing

100% Polyester

Mellohide

Flame Resistance

Manufactured to meet the following flammability* requirements:

CA TB 117-2013
(Section 1-Cover Fabric)


NFPA 260

UFAC Class 1

FMVSS 302

IMO MSC 88/26/ADD.
2 PART 8 (3.1 and 3.2)

* This term and corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.



IMO MED 164.144/11/0

Care and Cleaning Instructions

This product has been developed to emulate the look and feel of soft leather. The unique super dull finish is designed to be low burnishing, non-polishing and resistant to ultra violet exposure. Allante vinyls have superb tailoring qualities, which make pre-heating and steaming unnecessary and not recommended in the fabrication process. Because of the special leather-like finish, additional precautions should be observed when processing and cleaning. Please avoid contact with marking inks, glues and other staining materials that may damage vinyl during the manufacturing process. Protecting seating with a clean polyethylene cover, as is common in the automotive industry, should enable you to deliver a stain free unit to the customer.

If despite all precautions, staining material does come in contact with Allante vinyls, cleaning should be immediate and should follow these instructions:

- Dry soil, Dust and Dirt, Dried on Dirt: Remove with soft cloth dampened with water.
- Variation in Surface Gloss: Wipe with a soft cloth dampened with water. Allow to air dry.
- Stubborn Dirt: Wash with a soft cloth moistened with a mild soap and water. Rinse with clean water.
- Stubborn Spots and Stains: Spray with either Formula 409®, or Tannery Car Care Cleaner®, wiping with a soft cloth. Rinse with clean water.
- Liquid Spills: Wipe immediately with a clean absorbent cloth. Rinse with clean water.
- Food, Grease, and Oily Stains: Spray immediately using either Formula 409®, or Tannery Car Care Cleaner®, wiping with a soft cloth. Take care not to extend the area of contamination beyond its original boundary. Rinse with clean water.

Allante Vinyls should be periodically cleaned to maintain their appearance and prevent build-up of dirt and contaminants. Any stain, spill or soiling should be cleaned up promptly to prevent the possibility of permanent staining. When cleaning, always rub gently.

Caution: Powdered abrasives, abrasive cleaners, and steel wool damage vinyl, as do strong solvents, lacquer solvents and inks. Lotions, suntan oil, waxes and polishes, etc., contain oils and dyes that can cause stiffening and staining of vinyls. Never use heat guns or hair dryers.

Note: Stronger cleaners, detergents, and solvents may be effective in stain removal, but can cause either immediate damage or slow deterioration. Many such materials are wrongly recommend in marine and other related industries. The use of such cleaners is at the owner's own risk.

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing, but it is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with the laws and procedures applicable to the safe handling and use of this material.

888-MORBERN
www.morbern.com



Allante



Morbern is an ISO
9001:2015 Certified
Producer
©2020 Morbern, Inc.