



# Allante Collection

Allante, Carrara, Prodigy



Morbern

# Allante



AL-901 Cayenne



AL-846 Bisque




AL-891 Harvest



AL-892 Magnolia



AL-810 White



AL-827 Sea Oyster



AL-854 Lt. Parchment



AL-894 Meadow



AL-893 River Blue



AL-844 Cream



AL-862 Lt. Neutral



AL-808 Grey



AL-896 Sea Cruise



AL-902 Butterscotch



AL-864 Lt. Sand



AL-895 Hideaway



AL-809 Nu-Shale



AL-898 Parrot



AL-897 Reef



AL-904 Mango



AL-903 Twine




AL-824 Nu-Antelope



AL-874 Lt. Sandlewood



AL-899 Khaki



AL-890 Tundra



AL-901 Cayenne




AL-868 Teak




AL-900 Tumbleweed



AL-872 Med. Neutral



AL-856 Pearl Grey



AL-816 Cadet Blue



AL-877 Nu-Red




AL-860 Beechwood



AL-876 Med. Beige



AL-835 Med. Dk. Pewter




AL-870 Med. Grey



AL-806 Ash




AL-836 Wine



AL-838 Cinnamon



AL-828 Elephant



AL-804 Charcoal




AL-821 Regimental Blue




AL-818 Galaxy



AL-832 Burgundy



AL-840 Espresso




AL-802 Black

# Allante Collection

## Prodigy



PRO-686 Maple



PRO-680 White



PRO-681 Bisque




PRO-682 Lt. Neutral




PRO-699 Grey




PRO-683 Cream



PRO-684 Lt. Sand



PRO-685 Lt. Sandlewood




PRO-677 Med. Grey




PRO-690 Ochre



PRO-688 Paprika



PRO-696 Artichoke



PRO-675 Cosmic



PRO-694 Crimson




PRO-693 Nu-Red



PRO-691 Serrano



PRO-687 Empire Tan



PRO-697 Basil




PRO-676 Sailor



PRO-695 Espresso




PRO-678 Charcoal



PRO-689 Equestrian



PRO-692 Java



PRO-698 Hemlock



PRO-679 Black

## Carrara



CR-510 Buck



CR-505 Parchment



CR-504 Gold



CR-507 Antelope




CR-501 Steel Blue



CR-509 Tan



CR-506 Camel



CR-511 Charcoal



CR-500 Black



CR-508 Burgundy



CR-502 Dark Green



CR-503 Forest Green

## Specifications

### Allante and Carrara:

- Roll Width: 54 inches
- Roll Size: 40 yards
- Weight: 29.25 ± 2 oz per linear yard
- Thickness: 45 ± 5 mils

### Prodigy:

- Roll Width: 54 inches
- Roll Size: 40 yards
- Weight: 30.75 ± 2 oz per linear yard
- Thickness: 42 ± 5 mils

Cold Crack: -25°F

1000 Hours WeatherOmeter

Abrasion Resistance: No significant wear after 100,000 double rubs with #8 cotton duck using the Wyzenbeek test method

## Features & Benefits

- Mildew Resistant
- Made in North America
- Formulated without Ortho-Phthalates
- Bromine-free, No Halogenated Flame Retardants (HFRs)
- REACH compliant
- RoHS compliant
- No heavy metals
- No bisphenol A (BPA)
- No Mercury
- No Ozone Depleting Chemicals
- No PBT's (Persistent Bio accumulative and Toxic Chemicals)
- Contains bio-based renewable ingredients

## Content

Vinyl

## Backing

100% Polyester

## Flame Resistance

Manufactured to meet the following flammability\* requirements:

Cal TB 117-2013  
(Section 1-Cover Fabric)

FMVSS 302

UFAC Class 1

NFPA 260

IMO MSC 88/26/ADD. 2 Part 8 (3.1 and 3.2)

\* This term and corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

## Recommended Applications

Residential/Home Office  
Hotel/Motel  
Corporate  
Public Spaces  
Work Station  
Automotive  
RV

## Care and Cleaning Instructions

This product has been developed to emulate the look and feel of soft leather. The unique super dull finish is designed to be low burnishing, non-polishing and resistant to ultra violet exposure. Allante vinyls have superb tailoring qualities, which make pre-heating and steaming unnecessary and not recommended in the fabrication process. Because of the special leather-like finish, additional precautions should be observed when processing and cleaning. Please avoid contact with marking inks, glues and other staining materials that may damage vinyl during the manufacturing process. Protecting seating with a clean polyethylene cover, as is common in the automotive industry, should enable you to deliver a stain free unit to the customer.

If despite all precautions, staining material does come in contact with Allante vinyls, cleaning should be immediate and should follow these instructions:

- Dry soil, Dust and Dirt, Dried on Dirt: Remove with soft cloth dampened with water.
- Variation in Surface Gloss: Wipe with a soft cloth dampened with water. Allow to air dry.
- Stubborn Dirt: Wash with a soft cloth moistened with a mild soap and water. Rinse with clean water.
- Stubborn Spots and Stains: Spray with either Formula 409®, or CRC 40173 Tannery Leather, Vinyl & More Cleaner & Conditioner, wiping with a soft cloth. Rinse with clean water.
- Liquid Spills: Wipe immediately with a clean absorbent cloth. Rinse with clean water.
- Food, Grease, and Oily Stains: Spray immediately using either Formula 409®, or CRC 40173 Tannery Leather, Vinyl & More Cleaner & Conditioner, wiping with a soft cloth. Take care not to extend the area of contamination beyond its original boundary. Rinse with clean water.

Allante Vinyls should be periodically cleaned to maintain their appearance and prevent build-up of dirt and contaminants. Any stain, spill or soiling should be cleaned up promptly to prevent the possibility of permanent staining. When cleaning, always rub gently.

Caution: Powdered abrasives, abrasive cleaners, and steel wool damage vinyl, as do strong solvents, lacquer solvents and inks. Lotions, suntan oil, waxes and polishes, etc., contain oils and dyes that can cause stiffening and staining of vinyls. Never use heat guns or hair dryers.

Note: Stronger cleaners, detergents, and solvents may be effective in stain removal, but can cause either immediate damage or slow deterioration. Many such materials are wrongly recommend in marine and other related industries. The use of such cleaners is at the owner's own risk.

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing, but it is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with the laws and procedures applicable to the safe handling and use of this material.



800.543.0448



Morbern is an ISO  
9001:2015 Certified  
Producer  
©2020 Morbern, Inc.

# Allante Collection