



8 and 13 ounce Acrylic Coated Flame Retardant Polyester



751 Raven Black (13 oz)
751-LT Raven Black (8 oz)



710-LT Royal Blue* (8 oz)
710 Royal Blue* (13 oz)



779 Chocolate Brown (13oz)
779-LT Chocolate Brown (8oz)



719 Tan (13oz)
719-LT Tan (8oz)



740 Hunter Green* (13oz)
740-LT Hunter Green*(8oz)




765 White (13oz)
765-LT White (8oz)



776 Burgundy* (13oz)
776-LT Burgundy* (8oz)



707 Ivory (13oz)
707-LT Ivory (8oz)



783 Silver Gray (13oz)
783-Lt Silver Gray (8oz)



731 Ocean Blue (13oz)
731-LT Ocean Blue (8oz)



743 Terra Cotta (13oz)
743-LT Terra Cotta (8oz)



736 Red (13oz) †*
736-LT Red (8oz) †*



Marlen Textiles

* Premium Color, subject to change

To order 13 ounce Top Gun FR use 7xx number. To order 8 ounce Top Gun FR Lite use 7xx-LT.



Top Gun FR is an acrylic coated, 100% woven flame retardant polyester fabric (600 denier) utilizing a proprietary formula and process to coat the top and bottom, allowing the fabric to be completely reversible. Top Gun FR meets most known flame retardant specifications, both initial and leaching. That means that unlike other fabrics, you don't have to worry about still meeting a flame specification after it has been exposed to the elements. As the part of the Top Gun family of premium coated fabrics, it is characterized by excellent strength, durability, tear and abrasion resistance, dimensional stability, UV and mildew resistance, making Top Gun FR the ultimate flame retardant coated fabric. Top Gun FR is perfect for awnings, tents, gazebos, canopies or any application requiring colorfastness and flame resistance.

Top Gun FR, a hot alternative in flame retardant fabrics.

TECHNICAL DATA

Characteristic	TOP NOTCH FR®	TOP GUN FR®	TOP GUN FR LITE®	ODYSSEY FR®	ODYSSEY OPEN®
Width, inches	60	62	62	64	64
Roll Size, yards	50	45	50	100	100
Weight, oz/yard ²	11.5	13.0	8.0	7.25	5.75
Tensile (lbf), Warp x Fill	500 x 240	498 x 380	275 x 200	300 x 240	300 x 215
Tongue Tear (lbf), Warp x Fill	24 x 14	25 x 18	12 x 10	12 x 12	14.5 x 12
Spray Rating	90+	90+	90+	90+	n/a
3 Drop Rating (cm)	90	70	60	21	0
Warranty Period (years)	8	8	5	3	3
Shrinkage (%), Warp x Fill	0 x 0	0 x <1	<1 x <1	0 x <1	<1 x <1.25
Stretch (%), Warp x Fill	<1 x <1	<1 x <1	<1 x <1.25	<1 x <1.25	<1 x <1.5
Flame Retardant Specification					
MVSS-302	X	X	X	X	X
NFPA 701	X	X	X	X	
California State Fire Marshall	X	X	X	X	
CPAI 84	X	X	X	X	
CAN/ULC-S109-03	X	X	X	X	
FAA/FAR 25.853	X	X	X	X	



miami[™]
CORPORATION

miamicorp.com | 800.543.0448